

Product datasheet

Specifications



Network Power supply with battery backup, 12Vdc, 1A, CEE7, lithium battery

CP12010LI-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage	220 V 230 V 240 V
Main Output Voltage	12 V DC
Rated power in W	12 W
Rated power in VA	12 VA
Battery type	Li-Ion (Lithium-Ion)

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

Height	7.8 cm
Width	4.8 cm
Depth	7.6 cm
Product weight	0.2 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Output

Maximum configurable power in W	12 W
---------------------------------	------

Conformance

Standards	EN 55024 EN 60950
-----------	----------------------

Environmental

Ambient air temperature for operation 0...40 °C

Relative humidity 5...95 %

Ambient air temperature for storage -15...60 °C

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 11.3 cm

Package 1 Width 9.9 cm

Package 1 Length 5.2 cm

Package 1 Weight 0.28 kg

SCC14 10731304344091

Offer Sustainability

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information [Yes](#)

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)