

# Lembar data produk

Spesifikasi



APC Smart-UPS On-Line,  
1500VA/1500W, Tower, 230V,  
6x IEC C13 outlets, SmartSlot,  
Extended runtime, Rail kit excluded

SRT1500XLI

## Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1500 W
Rated power in VA	1500 VA
Input Connection Type	IEC 60320 C14
Output connection type	6 IEC 60320 C13
Cable length	1.83 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

## Batteries & Runtime

Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Battery voltage	48 V
Battery charger power	108 W rated
Battery power in VAh	324 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC155</a>

<b>Battery option</b>	SRT48BP 1 972 VAh SRT48BP 2 1620 VAh SRT48BP 3 2268 VAh SRT48BP 4 2916 VAh SRT48BP 5 3564 VAh SRT48BP 6 4212 VAh SRT48BP 8 5508 VAh SRT48BP 10 6804 VAh
-----------------------	--

<b>Extended runtime</b>	1
-------------------------	---

## General

<b>Product web sub-family</b>	High density
-------------------------------	--------------

<b>Number of power module free slots</b>	0
--	---

<b>Number of power module filled slots</b>	0
--	---

<b>Redundant</b>	No
------------------	----

## Physical

<b>Colour</b>	Black
---------------	-------

<b>Height</b>	43.2 cm
---------------	---------

<b>Width</b>	8.5 cm
--------------	--------

<b>Depth</b>	50.5 cm
--------------	---------

<b>Product weight</b>	20.5 kg
-----------------------	---------

<b>Mounting preference</b>	No preference
----------------------------	---------------

<b>Mounting mode</b>	Rack-mounted with kit
----------------------	-----------------------

<b>Two post mountable</b>	0
---------------------------	---

<b>USB compatible</b>	Yes
-----------------------	-----

<b>Mounting position</b>	Vertical
--------------------------	----------

## Input

<b>Network frequency</b>	40...70 Hz auto-sensing
--------------------------	-------------------------

<b>Input voltage limits</b>	100...275 V
-----------------------------	-------------

## Output

<b>Maximum configurable power in W</b>	1500 W
--	--------

<b>Harmonic distortion</b>	Less than 2 %
----------------------------	---------------

<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
-------------------------	---------------------------------

<b>Crest factor</b>	3 : 1
---------------------	-------

<b>UPS type</b>	Double conversion online
-----------------	--------------------------

<b>Wave type</b>	Sine wave
------------------	-----------

<b>Bypass type</b>	Built-in bypass
--------------------	-----------------

<b>Maximum configurable power in VA</b>	1500 VA
---	---------

## Conformance

<b>Product certifications</b>	CE EAC
-------------------------------	-----------

<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	74.9 cm
Package 1 Length	59.4 cm
Package 1 Weight	29.6 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

**Penggantian yang disarankan**