

[Get a Quote](#)

Overview

- Sixteen 10/100 Mbps Fast Ethernet ports
- Compact design for placement virtually anywhere
- Plug and play technology for simple setup
- Fanless design provides silent operation

Specification

DES-1016A Specification	
100Base-TX Interface	16
Auto MDI/MDIX	Yes
Console Port	No
RJ-45 Management Port	No
Alarm Port	No
CompactFlash (CF) Card Slot	No
Secure Digital (SD) Card Slot	No
Switching Capacity	3.2 Gbps
Max. Packet Forwarding Rate	2.38 Mpps
Dimension	155.7 × 122 × 41 mm
Operation Temperature	0 ~ 40 °C
Storage Temperature	-40 to 70 °C
Operation Humidity	10% ~ 90% RH
Storage Humidity	5% ~ 90% RH
Maximum Power Consumption	2.69 W
Power Input	AC: 100V ~ 240V
Packet Buffer Size	2 MB
FAN	Fanless

Want to Buy

[Order Now](#)[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com