

# Product datasheet

Specifications

## 10A 250V 2 Gang 2 Way Switch

KB32\_WE\_G3



### Main

Range	Vivace
Product or component type	Switch
Device short name	KB32
Device application	Control switch
Additional switch application	On/off switching
Number of rocker	2
Switch function	2-way
Colour tint	White

### Complementary

Technology type	Electromechanical
Device presentation	Complete product
Actuator	Rocker
Number of gangs	2 gangs White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Surface finish	Glossy
Surface treatment	Untreated
[Ue] rated operational voltage	220...250 V
Type of packing	Plastic bag
Network type	AC
Quantity per set	1
Sale per indivisible quantity	1
Rated current	16 AX
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5

<b>Fixing center</b>	60.3 mm
<b>Connections - terminals</b>	Screw terminal
<b>Embedding depth</b>	25 mm
<b>Number of terminals</b>	6  16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent 16 A at 250 V AC, resistive  250 V AC
<b>Network frequency</b>	50/60 Hz
<b>Contacts material</b>	Brass and phosphor bronze  6 screw terminals
<b>Terminal identifier</b>	COM L2 L1
<b>Tightening torque</b>	0.4 N.m
<b>Clamping connection capacity</b>	<= 2.5 mm <sup>2</sup> for rigid or stranded cable(s)
<b>Wire stripping length</b>	12 mm
<b>Width</b>	86 mm
<b>Height</b>	86 mm
<b>Depth</b>	37 mm

## Environment

<b>Standards</b>	MS IEC 60669-1 IEC 60669-1 SS 227
<b>Product certifications</b>	SNI
<b>Ambient air temperature for operation</b>	-5...40 °C
<b>Relative humidity</b>	0...95 %
<b>Operating altitude</b>	0...2000 m
<b>Environmental characteristic</b>	Indoor use
<b>IP degree of protection</b>	IP20

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.8 cm
<b>Package 1 Width</b>	8.6 cm
<b>Package 1 Length</b>	8.6 cm
<b>Package 1 Weight</b>	77.0 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	8
<b>Package 2 Height</b>	9.5 cm
<b>Package 2 Width</b>	15.0 cm
<b>Package 2 Length</b>	19.0 cm
<b>Package 2 Weight</b>	780.0 g
<b>Unit Type of Package 3</b>	CAR

<b>Number of Units in Package 3</b>	80
<b>Package 3 Height</b>	21.0 cm
<b>Package 3 Width</b>	32.5 cm
<b>Package 3 Length</b>	50.0 cm
<b>Package 3 Weight</b>	7800.0 g

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)