# **Product datasheet**

Specifications





## 115/240V Shaver Unit

KBT727V\_WE

#### Main

Range	Vivace
Product or component type	Shaver socket
Device short name	KBT
Device application	Power supply
Device presentation	Complete mechanism
Colour tint	Wall: white

Complementary	
Number of gangs	2 gangs
	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	40 mm
Rated current	at 115/240 V AC
Input voltage	115 V AC
Output voltage	240 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L N E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm²
Width	146 mm

Height	86 mm
Depth	47 mm
Environment	
Standards	IEC 61558-2-5
Ambient air temperature for operation	-540 °C
Ambient air temperature for storage	060 °C
Relative humidity	095 %
Operating altitude	02000 m
Environmental characteristic	Indoor use
IP degree of protection	IP21
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	4.9 cm
Package 1 Length	14.6 cm
Package 1 Weight	671.5 g
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	2 cm
Package 2 Weight	1.413 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	20
Package 3 Height	31.5 cm
Package 3 Width	50 cm
Package 3 Length	50 cm
Package 3 Weight	13680 g
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Environmental Disclosure Product Environmental Profile

### **Contractual warranty**

Warranty 18 months

Recommended replacement(s)