

17" Rack LCD Console with Integrated 16 Port Analog KVM Switch

AP5816

Ov	er	VI	e	W
----	----	----	---	---

Presentation	The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.

Lead time Usually in Stock

Main

wain	
Main Input Voltage	120 V 240 V
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Cable length	6 ft (1.83 m)
Number of cables	1
Provided equipment	USB KVM cable Single user rack mount kit PS2 KVM cable NEMA 5-15 power cord Installation guide Firmware upgrade cable Documentation CD

Physical

•	
Color	Black
Height	1.69 in (4.3 cm)
Width	19.02 in (48.3 cm)
Depth	27.99 in (71.1 cm)
Net Weight	30.86 lb(US) (14 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Maximum Mounting Depth	41.33 in (104.98 cm)
Minimum Mounting Depth	26.77 in (68 cm)

Input

Input Frequency 50/60 Hz

C13-C14 power cord

Conformance

Product Certifications	cUL Listed C-tick CE Industry Canada KCC UL Listed VDE TAA compliance
Standards	EN 60950 FCC Part 15 class A IEC 60950

Environmental

Ambient Air Temperature for Operation

32...104 °F (0...40 °C)

Supported Hardware

Display colour	16 colours
Display size	337.9 (H) x 270.3 (V) 17 inch
Trackball Type	PS/2 Touchpad USB mouse
Display Type	LCD display

Ordering and shipping details

GTIN 731304278818

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.12 in (13 cm)
Package 1 Width	32.68 in (83 cm)
Package 1 Length	26.18 in (66.5 cm)
Package 1 Weight	44.40 lb(US) (20.14 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65 WARNING: This product can expose you to chemicals including: Diisononyl phthalat known to the State of California to cause cancer. For more information go to www.Po		
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Lead free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Take-back	Take-back program available	

Contractual warranty

Warranty

2 years repair or replace

Recommended replacement(s)