

AvatarOn, USB charger + 2 socketoutlet, 2P, 16A, Dark Grey

E8342616USB_DG

Main

Product or component type	USB charger + socket-outlet
Fixing mode	By screws

Complementary	
Outlet standard	China
Outlet standard description	With earthing contact
Integrated connection type	2 socket-outlet 250 V AC 16 A 50/60 Hz 1 USB type A 5 V DC 2.1 A
Device mounting	Flush Surface
Device presentation	Complete product
Mounting support	Mounting box
Outlet poles configuration	2P with shutter
Colour tint	Dark grey
Surface finish	Glossy
Surface treatment	Untreated
Ambient air temperature for storage	-2060 °C
Protection type	Current protection
Dielectric strength	2000 V
Ambient air temperature for operation	-535 °C
Service life in cycles	5000 cycles
Connections - terminals	Screw terminal
Number of terminals	3
Screwdriver shape	Phillips combined
Number of cables	2
Clamping connection capacity	1.54 mm² for rigid cable(s) 1.54 mm² for stranded cable(s) 1.54 mm² for flexible cable(s)
Material	PC (polycarbonate): grid plate PC (polycarbonate): surround
Wire stripping length	12 mm

Height	86 mm	
Width	86 mm	
Depth	38.2 mm	
Standards	UL 498 UL 94 UL 1310	

Environment

IP degree of protection IP20

Packing Units

· ····································	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	8.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	135 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	19 cm
Package 2 Length	19.5 cm
Package 2 Weight	1.08 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	48
Package 3 Height	21 cm
Package 3 Width	30 cm
Package 3 Length	39.5 cm
Package 3 Weight	6.48 kg

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Compliant EU RoHS Declaration
Yes
Yes
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Yes
Product Environmental Profile

Recommended replacement(s)