

Lembar data produk

Spesifikasi

Comb busbar, Easy9 XP, 1P, 63 A, 12 modules



EZ9XPH112

Main

Range	Easy9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	12

Complementary

Number of ways	12 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	2 end piece
[Ie] rated operational current	63 A at 40 °C
[Ue] rated operational voltage	230 V AC 50 Hz Ph/N
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-1
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	220 mm
Colour	Light grey (RAL 7035)
Range compatibility	Easy9 (Easy9 XP)

Environment

Standards	IEC 60439-1 IEC 60664
Fire resistance	850 °C (30 s) conforming to IEC 60695-2-1

Pollution degree	2
------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	1.5 cm
Package 1 Length	21.5 cm
Package 1 Weight	34 g
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Height	5.7 cm
Package 2 Width	8.5 cm
Package 2 Length	24.7 cm
Package 2 Weight	587 g
Unit Type of Package 3	S03
Number of Units in Package 3	270
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	11.045 kg

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Penggantian yang disarankan