

APC Home/Office SurgeArrest 5 outlets with 5V, 2.4A 2 port USB charger 230V Germany

PM5U-GR

Ov	er	VI	e	W
----	----	----	---	---

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Input Connection Type	Schuko CEE 7/7P
Cable length	1.83 m
Number of cables	1
Provided equipment	User manual

Physical

Colour	White
Height	5.58 cm
Width	37 cm
Depth	7.3 cm
Product weight	0.67 kg
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input power	2300 W
Network frequency	50 Hz
Maximum input current	10 A
Switching current capacity	10 A

Output

Number of power socket outlets	5
Outlet standard	Schuko CEE 7

Conformance

Product certifications CE

Equipment protection policy	Lifetime : 50000 euros
Environmental	
Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	050000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m
Surge Protection and Fi	1 ns common mode
Response time	1 ns common mode
Common mode rejection	40 dB
Peak current	24 kAcommon mode
Surge energy rate	918 J
Packing Units	
Unit Type of Package 1	PCE
	1
Number of Units in Package 1	5.8 cm
Number of Units in Package 1 Package 1 Height	
	40.5 cm
Package 1 Height Package 1 Width	
Package 1 Height	40.5 cm

Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	

Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

WEEEThe product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty Limited Lifetime (European Union countries only)

Recommended replacement(s)