

# Lembar data produk

Spesifikasi

**APC**

Green  
Premium™



## APC Performance SurgeArrest 6 outlets with 5V, 2.4A 2 port USB charger, 230V Germany

PM6U-GR

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Input Connection Type	Schuko CEE 7/7P
Cable length	2.00 m
Number of cables	1
Provided equipment	User manual

### Physical

Colour	White
Height	6.2 cm
Width	27.2 cm
Depth	11 cm
Product weight	0.75 kg
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Input power	2300 W
Network frequency	50 Hz
Maximum input current	10 A
Switching current capacity	10 A

### Output

Number of power socket outlets	6
Outlet standard	Schuko CEE 7

### Conformance

Product certifications	CE
------------------------	----

Equipment protection policy      Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...50000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	40 dB
Peak current	48 kA common mode
Surge energy rate	1836 J

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	16.5 cm
Package 1 Length	31 cm
Package 1 Weight	0.89 kg
SCC14	10731304313721

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	Limited Lifetime (European Union countries only)
----------	--

## Penggantian yang disarankan