

# Lembar data produk

Spesifikasi



## Acti 9 - Auxiliary contact iOF/SD+OF - 2OC - AC/DC

A9A26929

### Main

|                             |                                                                                                                                                                           |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product            | Acti9                                                                                                                                                                     |
| Product or component type   | Double OC or fault contact                                                                                                                                                |
| Device short name           | iOF/SD+OF                                                                                                                                                                 |
| Signal contacts composition | 2 C/O                                                                                                                                                                     |
| [In] rated current          | DC-12 1 A at 130 V, DC<br>DC-12 1.5 A at 60 V, DC<br>DC-12 2 A at 48 V, DC<br>DC-12 6 A at 24 V, DC<br>AC-12 3 A at 415 V, AC 50/60 Hz<br>AC-12 6 A at 240 V, AC 50/60 Hz |
| 9 mm pitches                | 1                                                                                                                                                                         |

### Complementary

|                                                  |                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                    | 500 V                                                                                                                                                                                                                                                                                                                                                   |
| [Uimp] rated impulse withstand voltage           | 4 kV                                                                                                                                                                                                                                                                                                                                                    |
| Local signalling                                 | Mechanical indicator                                                                                                                                                                                                                                                                                                                                    |
| Mounting mode                                    | Fixed                                                                                                                                                                                                                                                                                                                                                   |
| Mounting support                                 | DIN rail                                                                                                                                                                                                                                                                                                                                                |
| Comb busbar and distribution block compatibility | NO                                                                                                                                                                                                                                                                                                                                                      |
| Height                                           | 90 mm                                                                                                                                                                                                                                                                                                                                                   |
| Width                                            | 9 mm                                                                                                                                                                                                                                                                                                                                                    |
| Depth                                            | 73 mm                                                                                                                                                                                                                                                                                                                                                   |
| Product weight                                   | 43 g                                                                                                                                                                                                                                                                                                                                                    |
| Colour                                           | White                                                                                                                                                                                                                                                                                                                                                   |
| Connections - terminals                          | Screw clamp terminal (top and bottom) 2 cable(s) 2.5 mm <sup>2</sup> - rigid<br>Screw clamp terminal (top and bottom) 2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule<br>Screw clamp terminal (top and bottom) 1 cable(s) 0.5...2.5 mm <sup>2</sup> - flexible<br>Screw clamp terminal (top and bottom) 1 cable(s) 1...4 mm <sup>2</sup> - rigid |
| Wire stripping length                            | 10 mm                                                                                                                                                                                                                                                                                                                                                   |
| Tightening torque                                | 1 N.m                                                                                                                                                                                                                                                                                                                                                   |

### Environment

|           |                  |
|-----------|------------------|
| Standards | EN/IEC 60947-5-1 |
|-----------|------------------|

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Tropicalisation                       | 2 conforming to EN/IEC 60947-5-1 |
| Ambient air temperature for operation | -35...70 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 7.500 cm  |
| Package 1 Width              | 2.400 cm  |
| Package 1 Length             | 9.200 cm  |
| Package 1 Weight             | 50.000 g  |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 8.500 cm  |
| Package 2 Width              | 10.000 cm |
| Package 2 Length             | 27.000 cm |
| Package 2 Weight             | 693.000 g |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 120       |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 7.600 kg  |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

### Penggantian yang disarankan