

Lembar data produk

Spesifikasi



switch disconnecter iSW - 1P - 40 A - 240 V

A9S65140

Main

| | |
|---------------------------|---------------------|
| Range | Acti9 |
| Product name | Acti9 iSW |
| Product or component type | Switch disconnecter |
| Device short name | iSW |
| Device application | Isolation Control |
| Poles description | 1P |
| Utilisation category | AC-22A |
| Suitability for isolation | Yes |

Complementary

| | |
|--|----------------------------------|
| [Ie] rated operational current | 40 A at 240 V AC 50/60 Hz |
| [Ue] rated operational voltage | 240 V AC 50/60 Hz |
| [Icm] rated short-circuit making capacity | 4.2 kA switch-disconnector alone |
| [Icw] rated short-time withstand current | 1260 A |
| [Ui] rated insulation voltage | 250 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Control type | Toggle |
| Local signalling | ON/OFF indication |
| Contact position indicator | Yes |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | Top or bottom: YES |
| 9 mm pitches | 2 |
| Height | 85 mm |
| Width | 18 mm |
| Depth | 73 mm |

| | |
|-------------------------|--|
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 15000 cycles |
| Connections - terminals | Tunnel type terminals (top or bottom) - <= 1 x 50 mm ² - rigid Tunnel type terminals (top or bottom) - <= 1 x 35 mm ² - flexible Tunnel type terminals (top or bottom) - <= 1 x 35 mm ² - flexible with ferrule |
| Wire stripping length | 9 mm |
| Tightening torque | 3.5 N.m |

Environment

| | |
|---------------------------------------|---------------------------|
| Standards | IEC 60947-3 EN 60947-3 |
| IP degree of protection | IP20 |
| Pollution degree | 3 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.000 cm |
| Package 1 Width | 7.500 cm |
| Package 1 Length | 9.500 cm |
| Package 1 Weight | 83.800 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 8.500 cm |
| Package 2 Width | 10.000 cm |
| Package 2 Length | 22.000 cm |
| Package 2 Weight | 1.059 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 132 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 12.037 kg |

Offer Sustainability

| | |
|--------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |

| | |
|------------------------------------|---|
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Penggantian yang disarankan