

Key **Features**

- Auto Power Off
- 22,000:1 contrast ratio
- SuperColor™ Technology
- 5 colour modes
- Vertical Keystone



Product **Description**

The ViewSonic PA503SE offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 4,000 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of PA503SE reduces power consumption and extends the lamp life by up to 15,000 hours.



o14

- 1. Keypad
- 2. LED indicator
- 3. Lamp cover 4. Security lock
- 5. Zoom/Focus
- 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA
- 11. VGA out 12. Mini USB
- 13. Video
- 14. Kensington® Lock Slot
- 15. RS232

Visit Us

www.viewsonic.com

OTHERS

SPECIFICATION		0
Native Resolution:	800x600	Р
DC type:	DC3	i
Brightness:	4000 ANSI lumens	P
Contrast Ratio with SuperEco mode:	22000:1	C
Display Color:	1.07 Billion Colors	C
Light Source:	Lamp	
Light source life (Nor/SuperEco):	5000/15000	N C
Lamp Watt:	190W	
Lens:	F=2.56-2.68, f=22-24.1 mm	
Projection Offset:	120%+/-5%	L
Throw Ratio:	1.96~2.15	
Image size:	30" - 300"	
Throw Distance:	1.19m-13.11m(100" @3.98m)	S1
Keystone:	±40° (Vertical)	P
Optical Zoom:	1.1x	V
Audible Noise (Eco):	27dB	F
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	0
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	Д
Video Compatibility:	NTSC, PAL, SECAM	
Horizontal Frequency:	15K~102KHz	
Vertical Scan Rate:	23~120Hz	
INPUT		
Computer in (share with component):	2	
Composite:	1	
Audio-in (3.5mm):	1	
HDMI:	1 (Back)	
OUTPUT		
Monitor out:	1	
Audio out (3.5mm):	1	
Speaker:	2W	
CONTROL		
RS232:	1	
USB type mini B (Services):	1	

100-240V+/- 10%, 50/60Hz AC
Normal: 260W Standby: <0.5W
0~40°C
Brown
2.2kg
294x218x110mm
English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
1
1
1
QSG: 1 / CD: NA