

Key **Features**

- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- · Auto power off
- Vertical keystone



Product **Description**

The ViewSonic PA503XE offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 4,000 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of PA503XE reduces power consumption and extends the lamp life by up to 15,000 hours.



- 1. Keypad
- 2. LED indicator
- 3. Lamp cover 4. Security lock
- 5. Zoom/Focus
- 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA 11. VGA out
- 12. Mini USB
- 13. Video
- 14. Kensington® Lock Slot

15. RS232

o14

Visit Us

www.viewsonic.com

HERS

SPECIFICATION		ОТН
Native Resolution:	1024x768	Pow
DC type:	DC3	
Brightness:	4,000 ANSI Lumens	Pow
Contrast Ratio with SuperEco mode:	22000:1	Ope
Display Color:	1.07 Billion Colors	Car
Light Source:	Lamp	Net
Light source life (Nor/SuperEco):	5000/15000	Dim w/ad
Lamp Watt:	190W	
Lens:	F=2.56-2.68, f=22-24.1 mm	
Projection Offset:	120%+/-5%	Lan
Throw Ratio:	1.96~2.15	
Image size:	30" - 300"	
Throw Distance:	1.19m-13.11m(100" @3.98m)	STA
Keystone:	±40° (Vertical)	Pow
Optical Zoom:	1.1x	VGA
Audible Noise (Eco):	27dB	Ren
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	QS(OPT
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	Air I
Video Compatibility:	NTSC, PAL, SECAM	
Horizontal Frequency:	15K~102KHz	
Vertical Scan Rate:	23~120Hz	
INPUT		
Computer in (share with component):	2	
Composite:	1	
Audio-in (3.5mm):	1	
HDMI:	1 (Back)	
OUTPUT		
Monitor out:	1	
Audio out (3.5mm):	1	
Speaker:	2W	
CONTROL		
RS232:	1	
USB type mini B (Services):	1	

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
STANDARD ACCESSORY	
Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA
OPTIONAL ACCESSORY	
Air Filter:	RSPL

100-240V+/- 10%,