

ViewSonic® LAYAR LCD VX2728

Fitur Utama

- Fast IPS Display with HDR10
- AMD FreeSync™ Premium for smooth gameplay
- VESA AdaptiveSync for tear-free gaming experience
- VESA ClearMR for clarity of action
- Rapid 0.5ms MPRT for crisp image



Deskripsi Produk

No matter how often you game or when you game, you always win with the Omni VX2728. The triple certification of AMD FreeSync™ Premium, VESA Adaptive Sync, and VESA clearMR allows you to savor distortion-free gaming and enhanced clarity. The sharp frames and outstanding color performance are delivered by a fast IPS panel, while the VX2728's high 180Hz refresh rate supports smooth visuals and minimal input lag. You may think it doesn't get better than this, but it does. Not only will you get the job done — be it grueling gaming sessions, video and photo editing, or office assignments — you'll be working on a sleek, beautifully designed monitor.

Kunjungi Kami

www.viewsonic.com

TAMPILAN

Display Size (in.):	27
Viewable Area (in.):	27
Jenis Panel:	IPS Technology
Resolusi:	1920 x 1080
Jenis Resolusi:	FHD (Full HD)
Rasio Kontras Statis:	1,000:1 (typ)
Rasio Kontras Dinamis:	80M:1
Sumber cahaya:	LED
Kecerahan:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	2.5ms
Waktu Respon (GTG w / OD):	2.495ms
Response Time (MPRT):	0.5ms
Sudut Pandang:	178° horizontal, 178° vertical
Backlight Life (Jam):	30000 Hrs (Min)
Lengkungan:	Flat
Recommend timing Fv (Hz):	180
Input Fv (Max; Hz):	180
Variable Refresh Rate Technology:	FreeSync Premium, AdaptiveSync
Filter Cahaya Biru:	Yes
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 90% coverage (Typ) NTSC: 94% size (Typ) sRGB: 132% size (Typ)
Ukuran Piksel:	0.311 mm (H) x 0.311 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

KESESUAIAN

Resolusi PC (max):	1920x1080
Resolusi Mac® (maks):	1920x1080
Sistem Operasi PC:	Windows 10/11 certified; macOS tested
Resolusi Mac® (min):	1920x1080

KONEKTOR

3.5mm Audio Out:	1
HDMI 1.4:	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

AUDIO

Speaker Internal:	2Watts x2
-------------------	-----------

POWER

Mode Eco (Hemat):	20W
Eco Mode (optimized):	24W
Konsumsi (khas):	29W
Konsumsi (maks):	33W
Tegangan:	AC 100-240V
Stand-by:	0.3W
Sumber Daya listrik:	External Power Adaptor

PERANGKAT KERAS TAMBAHAN

Slot Kunci Kensington:	1
------------------------	---

KONTROL

Kontrol Fisik:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
Pada Tampilan Layar:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Suhu:	32°F to 104°F (0°C to 40°C)
Kelembaban (tanpa kondensasi):	20% to 90%

PEMASANGAN DI DINDING

VESA Compatible:	100 x 100 mm
------------------	--------------

SINYAL INPUT

Frekuensi Horizontal:	HDMI (v1.4): 30 ~ 166KHz, DisplayPort (v1.4): 30 ~ 193KHz
Frekuensi Vertikal:	HDMI (v1.4): 48 ~ 180Hz, DisplayPort (v1.4): 48 ~ 180Hz

VIDEO INPUT

Sinkronisasi Digital:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.4)
-----------------------	--

ERGONOMIS

Miring (Maju / Mundur):	-5° / 20°
-------------------------	-----------

BERAT (IMPERIAL)

Net (lbs):	9
Bersih Tanpa Dudukan (lbs):	8
Gross (lbs):	12.8

BERAT (METRIK)

Net (kg):	4.1
Jaring Tanpa Dudukan (kg):	3.7
Gross (kg):	5.8

DIMENSI (IMPERIAL) (WXHXD)

Kemasan (in.):	26.8 x 18.1 x 5.3
Fisik (in.):	24.2 x 17.9 x 7.2
Fisik Tanpa Berdiri (masuk):	24.2 x 14.3 x 1.8

DIMENSI (METRIK) (WXHXD)

Kemasan (mm):	680 x 460 x 135
Fisik (mm):	615 x 454 x 183
Physical Without Stand (mm):	615 x 364 x 46

UMUM

Regulasi:	RoHS, REACH, WEEE, BSMI, RCM, GEMS, VCCI, PSE, BIS
-----------	--

ISI PAKET:	VX2728 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
------------	--

PACKAGE CONTENTS (VSI):	VX2728 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------------	--

PACKAGE CONTENTS (VSE):	VX2728 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------------	--

PACKAGE CONTENTS (VSA):	VX2728 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------------	--

PACKAGE CONTENTS (VSCN):	VX2728 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
--------------------------	--

Daur Ulang / Pembuangan:	Please dispose of in accordance with local, state or federal laws.
--------------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--