

ViewSonic® LCD DISPLAY VP2468a

Key Features

- 100% sRGB and 100% Rec.709 colour coverage
- USB-C connectivity with 65W power delivery
- Daisy Chain supported for dual monitor setup
- World 1st TÜV SÜD tested color blindness mode
- Delta E < 2 colour accuracy



Product Description

Designed to deliver unmatched color accuracy crucial for professional applications, the ViewSonic VP2468a monitor displays your work with the vivid and lifelike color it deserves. With Pantone validated 100% sRGB color coverage, this monitor provides industry standard color accuracy to ensure accurate results. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port while the USB-C provides single cable connectivity for connecting and charging all peripherals and accessories. In addition to the future proof, connection with USB3.2 Gen 1, HDMI, DisplayPort, or DP allows you to daisy chain monitors from USB-C or DP ports for multi-monitor setups. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta < 2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. What's more, an advanced ergonomic design delivers customized comfort for increased productivity. Hardware calibration function is also available which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5.87ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	Adobe RGB: 85% size / 78% coverage (Typ) DCI-P3: 84% size / 84% coverage (Typ) EBU: 112% size / 99% coverage (Typ) REC709: 114% size / 100% coverage (Typ) SMPTE-C: 123% size / 100% coverage (Typ) NTSC: 80% size (Typ) sRGB: 114% size / 100% coverage (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
DisplayPort Out:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
Ethernet LAN (RJ45):	1

POWER

Eco Mode (Conserve):	8.94W
Eco Mode (optimized):	10.8W
Consumption (typical):	13.9W
Consumption (max):	15.4W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 90KHz
Frequency Vertical:	24 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	130
Swivel:	120°
Tilt (Forward/Back):	-5° / 21°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	13
Net Without Stand (lbs):	7.7
Gross (lbs):	19.3

WEIGHT (METRIC)

Net (kg):	5.9
Net Without Stand (kg):	3.5
Gross (kg):	8.8

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	27.2 x 15 x 8.1
Physical (in.):	21.2 x 16.61~20.44 x 8.5
Physical Without Stand (in.):	21.2 x 12.2 x 1.9

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	690 x 380 x 205
Physical (mm):	539 x 422~519.28 x 215
Physical Without Stand (mm):	539 x 311 x 48

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, RCM, GEMS, BIS, CCC, China RoHS, China Energy Label, CECP
--------------	--

PACKAGE CONTENTS:	VP2468A x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

Power Management:	Energy Star standards, EPEAT
-------------------	------------------------------