

Key **Features**

- 100Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- AMD FreeSync™ prevents screen tearing
- Full HD resolution for high detail



Product **Description**

The ViewSonic VX2716 features a crisp Full HD display paired with a hyper-responsive 100Hz refresh rate for smooth gaming. The 100Hz refresh rate loads more frames for sleek gameplay with less lag. A 1ms response time ensures your reactions are as fast as the game, helping you to claim more victories. AMD FreeSync™ virtually eliminates screen tearing and stuttering for the smoothest gaming experience possible.

Visit Us

www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	24 ~ 115KHz
Viewable Area (in.):	27	Frequency Vertical:	48 ~ 100Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	1920 x 1080	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Resolution Type:	FHD (Full HD)	ERGONOMICS	DisplayFort (V1.2)
Static Contrast Ratio:	1,000:1 (typ)	Tilt (Forward/Back):	-5° / 20°
Dynamic Contrast Ratio:	80M:1	WEIGHT (IMPERIAL)	0 , 20
Light Source:	LED	Net (lbs):	10.6
Brightness:	300 cd/m² (typ)	Net Without Stand (lbs):	9
Colors:	16.7M	Gross (lbs):	14.1
Color Space Support:	8 bit (6 bit + Hi-FRC)	WEIGHT (METRIC)	
Aspect Ratio:	16:9	Net (kg):	4.8
Response Time (MPRT):	1ms	Net Without Stand (kg):	4.1
Viewing Angles:	178° horizontal, 178° vertical	Gross (kg):	6.4
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W	XHXD)
Curvature:	Flat	Packaging (in.):	26.8 x 17.5 x 5.6
Refresh Rate (Hz):	100	Physical (in.):	24.1 x 17 x 9.3
Variable Refresh Rate	FreeSync	Physical Without Stand (in.):	24.1 x 14.3 x 1.9
Technology:	·	DIMENSIONS (METRIC) (WXI	
Blue Light Filter:	Yes	Packaging (mm):	680 x 445 x 143
Flicker-Free:	Yes	Physical (mm):	612 x 432 x 237
Color Gamut:	NTSC: 72% size (Typ) sRGB: 103% size (Typ)	Physical Without Stand (mm):	612 x 364 x 49
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	GENERAL	
Surface Treatment:	Anti-Glare, Hard Coating (3H)		cTUVus, FCC-B, ICES003, Energy
COMPATIBILITY	, iiii. Olaro, Hara Osaling (Ori)	Regulations:	Star, EPEAT, CEC, TUV S-Mark, NOM, Mexico Energy, CB, RoHS, WEEE, BSMI
PC Resolution (max):	1920x1080		VX2716 x1, 3-pin Plug (IEC C13 /
Mac® Resolution (max):	1920x1080	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, Quick Start Guide x1
PC Operating System:	Windows 10/11 certified; macOS tested	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Mac® Resolution (min):	1920x1080		*Warranty offered may differ from
CONNECTOR		Warranty:	market to market
3.5mm Audio Out:	1	Power Management:	Energy Star standards, EPEAT
HDMI 1.4:	1		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	15W		
Eco Mode (optimized):	17W		
Consumption (typical):	19W		
Consumption (max):	28W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.