

## Rainer EST-G26R2R2D8HSI6-H8S700WR

Processor	<b>2x Intel Xeon Gold 6226R (16C/32T,2.90GHz,22MbCache)</b> 1st and 2nd Gen Xeon Scalable Processor Family
Chipset	Intel PCH C261
Memory	<b>8x 64GB DDR4 RDIMM (Total 512GB)</b> Total Slots : 8 (4-channel per CPU, 4 DIMM per CPU) Capacity : Maximum up to 256GB RDIMM/Maximum up to 512GB LRDIMM/Maximum up to 1024GB
LR-DIMM 3DS	Memory Type : 2933/2666/2400 Memory Size : 32GB, 16GB, 8GB, 4GB RDIMM; 64GB, 32GB LRDIMM; 128GB, 64GB LR-DIMM
3DS	Actual memory frequency differs from Intel CPU types and memory module. Please check Intel official site for more detail about the memory types supported by each CPU.
Storage	<b>6x 2.4TB HDD 2.5" SAS 10K</b> SATA Controller : Intel® C621 12 x SATA3 6Gb/s ports (12 by 3 Mini-SAS Connector) Intel® Rapid Storage Technology Enterprise(RSTe) (For Linux/Windows) (Support Software RAID 0, 1, 5, 10 ) 4 SATA3 6Gb/s port by 1miniSAS connector (Marvell 88SE9230) Intel®VROC (For Linux/Windows) (Support Software RAID )
Networking	<b>4 x Intel® I210AT + 1 x Mgmt LAN</b>
Back I/O Ports	4x USB 3.0 ports 1x VGA port <b>4x RJ-45 GbE LAN ports</b> <b>1x RJ-45 Mgmt LAN port</b>  Rear Switch/LED: 1x Power switch 1x Message LED 1x HDD LED 1x Location LED 1x BMC LED 1x P5V LED
Case	Rackmount 2U 8 Bays Hotswap HDD SAS/SATA Dimension : 650 x 482.6 x 88.90 mm Weight : ±9Kg (Case only) Include Rail Kit
Power Supply	Redundant 2U 1+1 700W Pure 80+ GOLD

**RAINER**  
DYNAMIC SERVER SOLUTION



Gambar Hanya Ilustrasi

