

Product data sheet

Specifications



Switch Socket - 13A 250V - 3 phase 3 pole - flat pin - IP66 (grey)

S56C313GY

Main

Range	WPS
Product Or Component Type	Switch and socket-outlet
Colour Tint	Light grey
Motor M-Rating As3133	M80

Complementary

Control Type	Rotary
Material	PVC (polyvinyl chloride) UV stabilised
Surface Finish	Gloss
Width	101 mm
Height	203 mm
Rated Current	13 A
[Ue] Rated Operational Voltage	250 V
Network Frequency	50 Hz
Network Number Of Phases	3 phases
Number Of Gangs	2 gangs
Pin Number	3
Device Composition	Flat pin
Number Of Poles	3
Mounting Mode	Surface mounted

Environment

Ip Degree Of Protection	IP66
-------------------------	------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	10.3 cm
Package 1 Length	20.8 cm
Package 1 Weight	833.333 g
Unit Type Of Package 2	CAR

Number Of Units In Package 2	12
Package 2 Height	22 cm
Package 2 Width	30.3 cm
Package 2 Length	44 cm
Package 2 Weight	10000 g
Unit Type Of Package 3	P12
Number Of Units In Package 3	300
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	268000 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins